

***ULTI**THIN*

The ultimate thin surface course treatment



ULTITHIN

The ultimate thin surface course treatment

ULTITHIN is a polymer modified 6mm thin surface course treatment, suitable for laying on both urban and rural roads. Using high grade aggregates, it delivers outstanding durability with impressive reductions in road noise.

To find out how **ULTITHIN** can help you achieve longer-lasting results, quickly and cost effectively call **0800 1 218 218**

TARMAC.COM

ULTIMATE DURABILITY

Using high quality aggregates ULTITHIN maintains it's surface texture and ride qualities over the full product life.

IMPROVED FINISH

ULTITHIN is designed for enhanced workability to assist compaction and improve finish around areas of detail like ironwork and junctions

ENHANCED SUSTAINABILITY

ULTITHIN can be laid at a 15mm minimum thickness, providing a cost-effective solution and conserving scarce primary resources. It can provide a long lasting alternative to microasphalt or surface dressing treatments.

ULTIMATE VERSATILITY

As a thin overlay, ULTITHIN can avoid the need for planing. Where reprofiling is required, the thickness of a single layer can be between 15mm and 30mm. Above 30mm, a regulating layer should be laid.

ULTIMATE NOISE REDUCTION

ULTITHIN has an even negative texture to give the lowest achievable surface noise for this application.

ULTIMATE QUALITY

Our third party accredited ISO 9001 Systems ensure a consistently high quality product is supplied at all times.

ULTIMATE SUPPORT

At Tarmac, technical excellence comes as standard. Our technical experts can provide advice on material suitability and Contractor Laying Guidance Documents are also available.