


PA1
0541



No. KM 33619

BSI hereby grants to:

Tarmac Topblock Limited
Ballidon Quarry
Ashbourne
Derbyshire
DE6 1GU
United Kingdom

In respect of:

BS EN 771-3

Specification for masonry units - Aggregate concrete masonry units (Dense and light-weight aggregates)

the right and Licence to use the Kitemark in accordance with the Kitemark Licence Conditions of Contract governing the use of the Kitemark, as may be updated from time to time by BSI, and as approved by the Registrar under the Trade Marks Act 1994 (the "Conditions"). All defined terms in this Licence shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Licence provided at or from the above address.

For and on behalf of BSI:



Alastair Trivett, Managing Director, BSI Product Services – Global

First granted: 5 Mar 1996

Date: 11 Apr 2007

Page: 1 of 2



003

The licence remains the property of BSI and shall be returned immediately upon request. This licence does not expire. To check its validity telephone: +44 (0)1442 230442
BSI is incorporated by Royal Charter


BSI
Product Services

BSI Product Services

Maylands Avenue, Hemel Hempstead, Hertfordshire HP2 4SQ United Kingdom

Tel: +44 (0)1442 230442 Website: www.bsi-global.com

BSI Group Headquarters: 389 Chiswick High Road, London W4 4AL Tel: +44 (0)208 996 9000



No. KM 33619

Tarmac Topblock Limited

Ashbourne

BS EN 771 – 3 : 2003 Specification for masonry units – Part 3: Aggregate concrete masonry units (Dense light weight aggregates)

MASONRY UNITS (CATEGORY I)

Topcrete standard

Worksize – 440x100 – 215x215mm; **Configuration** – Solid, Cellular, Hollow; **Tolerance category** – D1; **Density** – gross 1950Kg/m³; **Compressive strength** – 3.6 – 17.5 N/mm²; **Moisture movement** – 0.50mm/m; **Water vapour permeability** - μ 5/15; **Reaction to fire** – Class A1

Topcrete paint quality

Worksize – 440x100 – 215x215mm; **Configuration** – Solid, Cellular, Hollow; **Tolerance category** – D1; **Density** – gross 1850Kg/m³; **Compressive strength** – 3.6 – 10.4 N/mm²; **Moisture movement** – 0.50mm/m; **Water vapour permeability** - μ 5/15; **Reaction to fire** – Class A1

Topcrete fair faced

Worksize – 440x90 – 215x215mm; **Configuration** – Solid, Cellular, Hollow; **Tolerance category** – D1; **Density** – gross 1900Kg/m³; **Compressive strength** – 7.3 – 17.5 N/mm²; **Moisture movement** – 0.50mm/m; **Water vapour permeability** - μ 5/15; **Reaction to fire** – Class A1

First granted: 5 Mar 1996

Date: 11 Apr 2007

Page: 2 of 2

The licence remains the property of BSI and shall be returned immediately upon request. This licence does not expire. To check its validity telephone: +44 (0)1442 230442
BSI is incorporated by Royal Charter

BSI
Product Services

BSI Product Services

Maylands Avenue, Hemel Hempstead, Hertfordshire HP2 4SQ United Kingdom
Tel: +44 (0)1442 230442 Website: www.bsi-global.com

BSI Group Headquarters: 389 Chiswick High Road, London W4 4AL Tel: +44 (0)208 996 9000