

SAFETY INFORMATION

NATURAL HYDRAULIC LIME

(Prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1: Identification of the substance or preparation

Substance Name	Hydraulic Lime
Synonyms:	Natural Hydraulic Lime, NHL
Chemical Name and Formula	n/a - inorganic multi-constituent substance
Trade Name	White Peak Natural Hydraulic Lime
CAS N°	85117 - 09 - 5
EINECS N°	285 - 561 - 1
Molecular Weight	n/a
Reach Registration No	01-2119475523-0000

1.2: Use of the substance

Please check the identified uses in table 1 of the Appendix of this SDS.

Uses advised against There are no uses advised against

1.3: Company identification

Name Tarmac Cement & Lime
Address Buxton Lime & Powders
 Tunstead House
 Buxton
 Derbyshire
 SK17 8TG

Phone +44 (0)1298 768555

E-mail of competent person responsible for SDS in the MS or in the EU: buxton.technical@tarmac.com

1.4: Emergency telephone

UK/European Emergency N° 999/112

BL&C Transport Emergency Contact No. +44 (0)1298 27500

Refer to Hospital Accident and Emergency Department

2: HAZARDS IDENTIFICATION

2.1: Classification of the Substance

2.1.1 Classification according to Regulation (EC) 1272/2008

STOT Single Exp. 3, Route of exposure: Inhalation
 Skin Irritation 2
 Eye Damage 1

2.1.2 Classification according to Directive 67/548/EEC

Xi - irritant

2.2 Label elements

2.2.1 Labelling according to Regulation (EC) 1272/2008

Signal word: Danger



Hazard pictogram:

Hazard statements:

H315: Causes skin irritation
 H318: Causes serious eye damage
 H335: May cause respiratory irritation

Precautionary statements:

P102: Keep out of reach of children
 P280: Wear protective gloves/protective clothing/eye protection/face protection
 P305+P351+P330: IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTRE or doctor/physician
 P302+P352: IF ON SKIN: Wash with plenty of water
 P261: Avoid breathing dust/spray
 P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 P501: Dispose of contents/container in accordance with current waste regulations

2.2.2 Labelling according to Directive 67/548/EEC

Indication of danger:

Xi irritant

Risk phrases:

R37: Irritating to respiratory system
 R38: Irritating to skin
 R41: Risk of serious damage to eyes

Safety phrases:

S2: Keep out of the reach of children
 S25: Avoid contact with eyes
 S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
 S37: Wear suitable gloves
 S39: Wear eye/face protection



2.3 Other hazards

The substance does not meet the criteria for PBT or vPvB substance.
 No other hazards identified.

3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1: Composition

Main constituent

30 - 65% w/w
 calcium dihydroxide

EINECS: 215-137-3

CAS: 1305-62-0

EINECS: 215-137-3

15 - 40% w/w

Name: di-calcium silicate

CAS: 10034-77-2

EINECS: 233-107-8

0 – 10% w/w

Name: Calcium carbonate
CAS: 1317-65-3
EINECS: 215- 79-6**Impurities**No impurities relevant for classification and labelling.
Small quantities of calcium oxide and impurities. Impurities in lime products will vary from source to source.**4: FIRST-AID MEASURES****4.1 General Advice**

No known delayed effects. Consult a physician for all exposures except for minor instances.

**Following Eye Contact** Rinse eyes immediately with plenty of water and seek medical advice.**Following Inhalation** Move source of dust or move person to fresh air. Obtain medical attention immediately.**Following Ingestion** Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention.**Following Skin Contact** Carefully and gently brush the contaminated body surfaces in order to remove all traces of product. Wash affected area immediately with plenty of water. Remove contaminated clothing. If necessary seek medical advice.**4.2 Most important symptoms and effects, both acute and delayed**

Hydraulic lime is not acutely toxic via the oral, dermal, or inhalation route. The substance is classified as irritating to skin and the respiratory tract, and entails a risk of serious damage to the eye. There is no concern for adverse systemic effects because local effects (pH effect) are the major health hazard.

4.3 Indication of any immediate medical attention and special treatment needed

Follow the advice given in section 4.1

5: FIRE-FIGHTING MEASURES**5.1.1: Suitable Extinguishing media**The product is not combustible. Use a dry powder, foam or CO₂ fire extinguisher to extinguish the surrounding fire.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.1.2: Unsuitable extinguishing media

Do not use water.

5.2: Special hazards arising from the substance or mixture

None

5.3: Advice for fire fighters

Avoid generation of dust. Use breathing apparatus. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

6: ACCIDENTAL RELEASE MEASURES**6.1: Personal precautions, protective equipment and emergency procedures****6.1.1: For Non-emergency personnel**

Ensure adequate ventilation. Keep dust levels to a minimum. Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8).

6.2: Environmental precautions

Contain the spillage. Keep the material dry if possible. Cover area if possible to avoid unnecessary dust hazard. Avoid uncontrolled spills to watercourses and drains (pH increase). Any large spillage into watercourses must be alerted to the Environment Agency or other regulatory body.

6.3: Methods and material for containment and cleaning up

In all cases avoid dust formation.
Keep the material dry if possible.
Pick up the product mechanically in a dry way.
Use vacuum suction unit, or shovel into bags.

6.4 Reference to other sections

For more information on exposure controls/personal protection or disposal considerations, please check section 8 and 13 and the Appendix of this safety data sheet.

7: HANDLING AND STORAGE**7.1: Precautions for safe handling****7.1.1: Protective Measures**

Avoid contact with skin and eyes. Wear protective equipment (refer to section 8 of this safety data sheet). Do not wear contact lenses when handling this product. It is also advisable to have individual pocket eyewash. Keep dust levels to a minimum. Minimise dust generation. Enclose dust sources, use exhaust ventilation (dust collector at handling points). Handling systems should preferably be enclosed. When handling bags usual precautions should be paid to the risks outlined in the Council Directive 90/269/EEC.

7.1.2: Advice on general occupational hygiene

Avoid inhalation or ingestion and contact with skin and eyes. General occupational hygiene measures are required to ensure safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no drinking, eating and smoking at the workplace. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home.

7.2: Conditions for safe storage, including any incompatibilities

The substance should be stored under dry conditions. Any contact with air and moisture should be avoided. Bulk storage should be in purpose-designed silos. Keep away from acids, significant quantities of paper, straw, and nitro compounds. Keep out of reach of children. Do not use aluminium for transport or storage if there is a risk of contact with water.

7.3: Specific end use(s)

Please check the identified uses in table 1 of the Appendix of this SDS.
For more information please see the relevant exposure scenario, available in the Appendix, and check '2.1: Control of worker' in the relevant exposure scenario section in the Appendix.

8: EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1: Control parameters**

SCOEL recommendation (SCOEL/SUM/137 February 2008; see Section 16.6):
Occupational Exposure Limit (OEL), 8 h TWA: 1 mg/m³ fine fraction dust of calcium dihydroxide
Short-term exposure limit (STEL), 15 min: 4 mg/m³ fine fraction dust of calcium dihydroxide
PNEC aqua = 490 µg/l
PNEC soil/groundwater = 1080 mg/l

8.2: Exposure controls




To control potential exposures, generation of dust should be avoided. Further, appropriate protective equipment is recommended. Eye protection equipment (e.g. goggles or visors) must be worn, unless potential contact with the eye can be excluded by the nature and type of application (i.e. closed process). Additionally, face protection, protective clothing and safety shoes are required to be worn as appropriate.

Please check the relevant exposure scenario, given in the Appendix.

8.2.1: Appropriate engineering controls

If user operations generate dust, use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne dust levels below recommended exposure limits.

8.2.2: Individual protection measures, such as personal protective equipment

- | | | | |
|----------|------------------------|---|---|
| 8.2.2.1: | Eye/face protection | Do not wear contact lenses. For powders, tight fitting goggles with side shields, or wide vision full goggles. It is also advisable to have individual pocket eyewash. | 

 |
| 8.2.2.2: | Skin protection | Since calcium dihydroxide is classified as irritating to skin, dermal exposure has to be minimised as far as technically feasible. The use of protective gloves (nitrile), protective standard working clothes fully covering skin, full length trousers, long sleeved overalls, with close fittings at openings and shoes resistant to caustics and avoiding dust penetration are required to be worn. | |
| 8.2.3.3: | Respiratory protection | Local ventilation to keep levels below established threshold values is recommended. A suitable particle filter mask is recommended, depending on the expected exposure levels - please check the relevant exposure scenario, given in the Appendix/available via your supplier. | |
| 8.2.2.4: | Thermal Hazards | The substance does not represent a thermal hazard, thus special consideration is not required. | |

8.2.3: Environmental Exposure Control

All ventilation systems should be filtered before discharge to atmosphere.
 Avoid releasing to the environment.
 Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority responsible for environmental protection or other regulatory body.
 For detailed explanations of the risk management measures that adequately control exposure of the environment to the substance please check the relevant exposure scenario, available via your supplier.
 For further detailed information, please check the Appendix of this SDS.

9: PHYSICAL AND CHEMICAL PROPERTIES

9.1: Information on basic physical and chemical properties

Appearance:	White or off-white (beige) fine powder
Odour:	odourless
Odour threshold:	not applicable
pH:	12.4 (saturated solution at 20 °C)
Melting point:	> 450 °C (study result, EU A.1 method)
Boiling point:	not applicable (solid with a melting point > 450 °C)
Flash point:	not applicable (solid with a melting point > 450 °C)
Evaporation rate:	not applicable (solid with a melting point > 450 °C)
Flammability:	non flammable (study result, EU A.10 method)
Explosive limits:	non explosive (void of any chemical structures commonly associated with explosive properties)
Vapour pressure:	not applicable (solid with a melting point > 450 °C)
Vapour density:	not applicable
Relative density:	2.24 (study result, EU A.3 method)
Solubility in water:	1844.9 mg/L (study results, EU A.6 method) result for Ca (OH) ₂
Partition coefficient:	not applicable (inorganic substance)
Auto ignition temperature:	no relative self-ignition temperature below 400 °C (study result, EU A.16 method)
Decomposition temperature:	When heated above 580°C, calcium dihydroxide decomposes to produce calcium oxide (CaO) and water (H ₂ O)
Viscosity:	not applicable (solid with a melting point > 450 °C)
Oxidising properties:	no oxidising properties (Based on the chemical structure, the substance does not contain a surplus of oxygen or any structural groups known to be correlated with a tendency to react exothermally with combustible material)

9.2: Other information

Not available

10: STABILITY AND REACTIVITY

10.1: Reactivity

In aqueous media Ca(OH)₂ dissociates resulting in the formation of calcium cations and hydroxyl anions (when below the limit of water solubility).

10.2: Chemical Stability

Under normal conditions of use and storage, hydraulic lime is stable.

10.3: Possibility of hazardous reactions

Reacts exothermically with acids. When heated above 580°C, calcium dihydroxide decomposes to produce calcium oxide (CaO) and water (H₂O): Ca(OH)₂ → CaO + H₂O. Calcium oxide reacts with water and generates heat. This may cause risk to flammable material.

10.4: Conditions to avoid

Minimise exposure to air and moisture to avoid degradation.

10.5: Incompatible Materials

Reacts exothermically with acids to form salts. Calcium dihydroxide reacts with aluminium and brass in the presence of moisture leading to the production of hydrogen.



10.6: Hazardous Decomposition Products

None.

Further information: Calcium dihydroxide reacts with carbon dioxide to form calcium carbonate, which is a common material in nature.

11: TOXICOLOGICAL INFORMATION

11.1: Information on toxicological effects

Toxicity endpoints	Outcome of the effects assessment
Acute toxicity	Hydraulic lime is not acutely toxic. Oral LD ₅₀ > 2000 mg/kg bw (OECD 425, rat, test substance Ca(OH) ₂ . results applicable to hydraulic lime by read-across) Dermal no data available Inhalation no data available Classification for acute toxicity is not warranted.
Skin irritation / corrosion	Eye irritation: Calcium dihydroxide entails a risk of serious damage to the eye (eye irritation studies (in vivo, rabbit). Based on experimental results, calcium dihydroxide requires classification as severely irritating to the eye [R41, Risk of serious damage to eye; Eye Damage 1 (H318 - Causes serious eye damage)]. Skin irritation: Calcium dihydroxide is irritating to skin (in vivo, rabbit). Based on experimental results, calcium dihydroxide requires classification as irritating to skin [R38, irritating to skin; Skin Irrit 2 (H315 - Causes skin irritation) These results applicable to hydraulic lime by read-across].
Respiratory or skin sensitisation	No data available. Calcium dihydroxide is considered not to be a skin sensitizer, based on the nature of the effect (pH shift) and the essential requirement of calcium for human nutrition. These results applicable to hydraulic lime by read-across. Classification for sensitisation is not warranted.
Germ cell mutagenicity	Bacterial reverse mutation assay (Ames test, OECD 471): Negative Mammalian chromosome aberration test: Negative In view of the omnipresence and essentiality of Ca and of the physiological non-relevance of any pH shift induced by lime in aqueous media, lime is obviously void of any genotoxic potential including germ cell mutagenicity. Classification for genotoxicity is not warranted.
Carcinogenicity	Calcium (administered as Ca-lactate) is not carcinogenic (experimental result, rat). The pH effect of calcium dihydroxide does not give rise to a carcinogenic risk. Human epidemiological data support lack of any carcinogenic potential of calcium dihydroxide. These results applicable to hydraulic lime by read-across. Classification for carcinogenicity is not warranted.

Toxicity for reproduction	<p>Calcium (administered as Ca-carbonate) is not toxic to reproduction (experimental result, mouse).</p> <p>The pH effect does not give rise to a reproductive risk.</p> <p>Human epidemiological data support lack of any potential for reproductive toxicity of calcium dihydroxide.</p> <p>Both in animal studies and human clinical studies on various calcium salts no reproductive or developmental effects were detected. Also see the Scientific Committee on Food (Section 16.6). Thus, calcium dihydroxide is not toxic for reproduction and/or development. These results applicable to hydraulic lime by read-across.</p> <p>Classification for reproductive toxicity according to regulation (EC) 1272/2008 is not required.</p>
STOT - single exposure	<p>From human data it is concluded that Ca(OH)₂ is irritating to the respiratory tract. As summarised and evaluated in the SCOEL recommendation (Anonymous, 2008), based on human data calcium dihydroxide is classified as irritating to the respiratory system [R37, Irritating to respiratory system; STOT SE 3 (H335 - May cause respiratory irritation) These results applicable to hydraulic lime by read-across].</p>
STOT - repeated exposure	<p>Toxicity of calcium via the oral route is addressed by upper intake levels (UL) for adults determined by the Scientific Committee on Food (SCF), being UL = 2500 mg/d, corresponding to 36 mg/kg bw/d (70 kg person) for calcium. Toxicity of Ca(OH)₂ via the dermal route is not considered as relevant in view of the anticipated insignificant absorption through skin and due to local irritation as the primary health effect (pH shift).</p> <p>Toxicity of Ca(OH)₂ via inhalation (local effect, irritation of mucous membranes) is addressed by an 8-h TWA determined by the Scientific Committee on Occupational Exposure Limits (SCOEL) of 1 mg/m³ fine fraction dust (see Section 8.1). These results applicable to hydraulic lime by read-across.</p> <p>Therefore, classification of hydraulic lime for toxicity upon prolonged exposure is not required.</p>
Aspiration hazard	<p>Hydraulic lime is not known to present an aspiration hazard.</p>

12: ECOLOGICAL INFORMATION

12.1: Toxicity

12.1.1: Acute/Prolonged toxicity to fish	<p>LC₅₀ (96h) for freshwater fish 50.6mg/l (calcium dihydroxide) LC₅₀ (96h) for marinewater fish 457mg/l (calcium dihydroxide)</p>
12.1.2: Acute/Prolonged toxicity to aquatic invertebrates	<p>EC₅₀ (48h) for freshwater invertebrates 49.1 mg/l (Ca (OH)₂) LC₅₀ (96h) for marinewater invertebrates 158 mg/l (Ca (OH)₂)</p>
12.1.3: Acute/Prolonged toxicity to aquatic plants	<p>EC₅₀ (72h) for freshwater algae 184.57 mg/l (Ca (OH)₂) NOEC (72h) for freshwater algae 48 mg/l (Ca (OH)₂)</p>
12.1.4: Toxicity to microorganisms e.g. bacteria	<p>At high concentrations through rise of pH calcium dihydroxide is used for disinfection of sewage sludges</p>
12.1.5: Chronic toxicity to aquatic organisms	<p>NOEC (14d) for marinewater invertebrates 42 mg/l (Ca (OH)₂)</p>
12.1.6: Toxicity to soil dwelling organisms	<p>EC₁₀/LC₁₀ or NOEC for soil microorganisms 2000 mg/kg soil dw (Ca (OH)₂)</p>
12.1.7: Toxicity to terrestrial plants	<p>NOEC (21d) for terrestrial plants 1080 mg/kg (Ca (OH)₂)</p>
12.1.8: General effect	<p>Acute pH effect. In excess of more than 1 gm/l may be harmful to aquatic life. pH value >12 will rapidly decrease as result of dilution and carbonation.</p>

13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment	<p>Disposal of hydraulic lime should be in accordance with local and methods national legislation. Processing, use or contamination of this product may change the waste management options. Dispose of container and unused contents in accordance with applicable member state and local requirements.</p> <p>The used packing is only meant for packing this product; it should not be reused for other purposes. After usage, empty the packing completely.</p>
----------------------	---

14: TRANSPORT INFORMATION

Hydraulic lime is not classified as hazardous for transport (ADR (Road), RID (Rail), IMDG /GGVSea (Sea)).

14.1:	UN No	Not regulated
14.2:	UN Proper Shipping Name	Not regulated
14.3:	Transport Hazard classes	Not regulated
14.4:	Packing Group	Not regulated
14.5:	Environmental hazards	None
14.6:	Special precautions for user	Avoid any release of dust during transportation, by using air-tight tanks
14.7:	Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not regulated

15: Regulatory information

15.1: Safety, health and environmental regulations/legislation specific for the substance

Authorisations:	Not required
Restrictions on use	None
Other EU Regulations	Hydraulic lime is not a SEVESO substance, not an ozone-depleting substance and not a persistent organic pollutant.
National regulations	None

15.2: Chemical Safety Assessment

A chemical safety assessment has been carried out for this substance.

16: OTHER INFORMATION

Data are based on our latest knowledge but do not constitute a guarantee for any specific product features and do not establish a legally valid contractual relationship.

16.1: Hazard Statements

H315: Causes skin irritation
 H318: Causes serious eye damage
 H335: May cause respiratory irritation

16.2: Precautionary Statements

P102: Keep out of reach of children
 P280: Wear protective gloves/protective clothing/eye protection/face protection
 P305+P351: IF IN EYES: Rinse cautiously with water for several minutes
 P310: Immediately call a POISON CENTRE or doctor/physician
 P302+P352: IF ON SKIN: Wash with plenty of soap and water
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray
 P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 P501: Dispose of contents/container in accordance with current waste regulations

16.3: Risk Phrases

R37: Irritating to respiratory system
 R38: Irritating to skin
 R41: Risk of serious damage to eyes

16.4: Safety Phrases

S2 Keep out of reach of children
 S25 Avoid contact with eyes
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
 S37 Wear suitable gloves
 S39 Wear eye/face protection

16.5: Abbreviations

EC₅₀: median effective concentration
LC₅₀: median lethal concentration
LD₅₀: median lethal dose
NOEC: no observable effect concentration
OEL: occupational exposure limit
PBT: persistent, bioaccumulative, toxic chemical
PNEC: predicted no-effect concentration
SCOEL: Scientific Committee on occupational exposure limits
STEL: short-term exposure limit
TWA: time weighted average
vPvB: very persistent, very bioaccumulative chemical

16.6: Key Literature References

Anonymous, 2006: Tolerable upper intake levels for vitamins and minerals Scientific Committee on Food, European Food Safety Authority, ISBN: 92-9199-014-0 [SCF document]

Anonymous, 2008: Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL) for calcium oxide (CaO) and calcium dihydroxide (Ca(OH)₂), European Commission, DG Employment, Social Affairs and Equal Opportunities, SCOEL/SUM/137 February 2008

16.7 Revision

This version produced in reference to Annex II of the REACH Regulation (EC) 1907/2006

DISCLAIMER

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.

APPENDIX: Exposure Scenarios

Available on request from the supplier