

HEMELITE

COURSING BRICKS

Highly versatile, lightweight aggregate blocks



HEMELITE

COURSING BRICKS

HEMELITE is a range of lightweight aggregate blocks available in a variety of formats and suited to a number of loadbearing applications. HEMELITE COURSING BRICKS are designed for use with the range of HEMELITE blocks.

LESS WASTAGE

Ideal for infilling over lintels and between floor joists.

CONSISTENT BACKGROUND

Provides a uniform background to receive plaster or render.

SOUND INSULATION

The density of Hemelite Coursing Bricks matches that of Hemelite blocks ensuring the sound insulation integrity of the wall.

FIRE

All Hemelite products conform to a fire rating of Class A1 to BS EN 13501.

PRODUCT PROPERTIES

PRODUCT	COMPRESSIVE STRENGTH N/mm ² *	BLOCK THICKNESS mm	FACE SIZES, mm LENGTH X HEIGHT	THERMAL CONDUCTIVITY λ (W/mK)	DRY DENSITY kg/m ³	UNIT WEIGHT kg**	NUMBER OF UNITS PER m ² OF WALL
COURSING BRICK	3.6	100	215 x 65	0.57	1450	2.1	60 (sold in packs of 416)
	7.3	100	215 x 65	0.57	1450	2.1	60 (sold in packs of 416)
		140	215 x 65	0.57	1450	2.9	60 (sold in packs of 312)
	10.4	100	215 x 65	0.57	1450	2.1	60 (sold in packs of 416)
		140 ⁽¹⁾	215 x 65	0.57	1450	2.9	60 (sold in packs of 312)

*Manufactured to Category 2 manufacturing control. **Unit weights which are given for design purposes, are approximate and calculated based on the specified dry density with a moisture content of 3% by weight added to provide equilibrium weights. (1) Subject to availability please check with Tarmac blocks sales team.

To find out more about our range of BLOCKS and the best solution for your project call **0345 606 2468**
Check out our U-value Calculator www.tarmac.com/u-value-calculator

TARMAC.COM