

Declaration of Performance DoP No.10

1. Unique identification code of product type: **See Tables 1 to 4 below.**
2. Type, batch or serial number or any other element allowing identification of the construction product:
The date of production that can be used for traceability is printed either on the packs of blocks or on the delivery note
3. Intended use: **In walls, columns, and partitions**
4. Name, registered trade name or registered trademark and contact address of the manufacturer:
Tarmac Building Products Limited, i10 Railway Drive, Wolverhampton, WV1 1LH
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 4**
7. Declared performance – See Tables 1-3 below.

Declaration of Performance – DoP No. 010

Table 1 - For foundation blocks please refer to Tarmac Building Products company literature for information on Sulfate class

Unique Identification Code	HEMELITE STD 3.6	HEMELITE STD 7.3	HEMELITE STD 10.4	HEMELITE CELLULAR 3.6	HEMELITE PQ 3.6	HEMELITE PQ 7.3	HEMELITE PQ 10.4	HEMELITE FOUNDATIO N 7.3	ULTRALITE 3.6 (Std & PQ)	AGGBLOCK LITE 7.3 (Std & PQ)	AGGBLOCK LITE FOUNDATION 7.3
Harmonised Technical Specification	EN 771-3:2011+A1:2015										
Essential Requirement	Declared performance										
Dimensions	As declared on delivery ticket										
Dimensional tolerances											
Category	D1	D1	D1	D1	D1	D1	D1	D1	D1	D1	D1
Flatness	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Plane parallelism	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Compressive Strength N/mm² (Cat II)	3.6	7.3	10.4	3.6	3.6	7.3	10.4	7.3	3.6	7.3	7.3
Configuration to EN 1996-1-1	Group 1	Group 1	Group 1	100mm Group 1 >100mm Group 2	Group 1	Group 1	Group 1	Group 1	Group 1	Group 1	Group 1
Moisture movement mm/m	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1
Shear bond strength N/mm² (tab value)	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
Water absorption	Not to be left exposed										
Gross dry density kg/m³	1450	1450	1450	1450	1450	1450	1450	1450	1100	1100	1100
Water vapour diffusion coefficient	5/15	5/15	5/15	5/15	5/15	5/15	5/15	5/15	5/15	5/15	5/15
Thermal conductivity W/mK ($\lambda_{10, dry}$) (P=50 %) (tabulated)	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.30	0.30	0.30
Durability against freeze/thaw	Not to be left exposed										

Declaration of Performance – DoP No. 010

Table 2 - For foundation blocks please refer to Tarmac Building Products company literature for information on Sulfate class

Unique Identification Code	TOPCRETE STD 7.3	TOPCRETE STD 10.4	TOPCRETE STD 17.5	TOPCRETE STD 22.5	TOPCRETE STD CELLULAR 3.6	TOPCRETE STD CELLULAR 7.3	TOPCRETE STD HOLLOW 3.6	TOPCRETE STD HOLLOW 7.3	TOPCRETE STD PQ 7.3
Harmonised Technical Specification	EN 771-3:2011+A1:2015								
Essential Requirement	Declared performance								
Dimensions	As declared on delivery ticket								
Dimensional tolerances									
Category	D1	D1	D1	D1	D1	D1	D1	D1	D1
Flatness	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Plane Parallelism	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Compressive Strength N/mm² (Cat II)	7.3	10.4	17.5	22.5	3.6	7.3	3.6	7.3	7.3
Configuration to EN 1996-1-1	Group 1	Group 1	Group 1	Group 1	100mm Group 1 >100mm Group 2	100mm Group 1 >100mm Group 2	Group 2	Group 2	Group 1
Moisture movement mm/m	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1
Shear bond strength N/mm² (tab value)	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
Water absorption	Not to be left exposed								
Gross dry density kg/m³	1950	1950	1950	1950	1950	1950	1950	1950	1950
Water vapour diffusion coefficient	5/15	5/15	5/15	5/15	5/15	5/15	5/15	5/15	5/15
Thermal conductivity W/mK ($\lambda_{10,dry}$) (P=50 %) (tabulated)	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Durability against freeze/thaw	Not to be left exposed								

Declaration of Performance – DoP No. 010

Table 3 – For foundation blocks please refer to tarmac Building Products company literature for information on Sulfate class

Unique Identification Code	TOPCRETE PQ 10.4	TOPCRETE PQ CELLULAR 3.6	TOPCRETE PQ CELLULAR 7.3	TOPCRETE PQ HOLLOW 3.6	TOPCRETE PQ HOLLOW 7.3	TOPCRETE RPW 7.3	TOPCRETE RPW 10.4	TOPCRETE FOUNDATION 7.3
Harmonised Technical Specification	EN 771-3:2011							
Essential Requirement	Declared performance							
Dimensions	As declared on delivery ticket							
Dimensional tolerances								
Category	D1	D1	D1	D1	D1	D1	D1	D1
Flatness	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Plane Parallelism	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Compressive Strength N/mm² (Cat II)	10.4	3.6	7.3	3.6	7.3	7.3	10.4	7.3
Configuration to EN 1996-1-1	Group 1	100mm Group 1 >100mm Group 2	100mm Group 1 >100mm Group 2	Group 2	Group 2	Group 1	Group 1	Group 1
Moisture movement mm/m	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1
Shear bond strength N/mm² (tab value)	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
Water absorption	Not to be left exposed							
Gross dry density kg/m³	1950	1950	1950	1950	1950	1950	1950	1600
Water vapour diffusion coefficient	5/15	5/15	5/15	5/15	5/15	5/15	5/15	5/15
Thermal conductivity W/mK ($\lambda_{10, dry}$) (P=50 %) (tabulated)	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.69
Durability against freeze/thaw	Not to be left exposed							

Declaration of Performance DoP No. 010

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



James Warwick
Technical Manager