

Declaration of Performance

DoP No. 025

1. Unique identification code of product type: **Tanking Render**
2. Type, batch or serial number or any other element allowing identification of the construction product: **The date of production, batch number and the name of the product printed on the bag.**
3. Intended use: **General purpose rendering mortar (GP) for internal and external use in wall, column, partition and ceiling finishes.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:-
Tarmac Building Products Limited, i10, Railway Drive, Wolverhampton, WV1 1LH
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 4**
7. In accordance with the harmonised standard **EN 998-1:2010**

8. Declared performance

Unique Identification Code	Tanking Render	Harmonised technical specification
Essential Characteristics	Performance	EN 998-1:2010
Reaction to fire (class)	Euroclass A1	
Capillary water absorption (category)	W2	
Adhesion (declared)	1.9 N/mm ² , FP C	
Water vapour diffusion coefficient (μ) (declared)	15/35	
Durability (against freeze/thaw): (declared)	Evaluation based on provisions valid in the intended place of use of the mortar	

Table 1

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Stuart Allerton – (Quality Systems Manager)



18th August 2014